

Speedzter 5

1394/ USB 2.0 combo interface Enclosure for 5.25" ATAPI devices

Reliable External Storage Device

With high-performance 1394/ USB 2.0 bridge adapter built-in, the Speedzter 5 can easily convert an internal ATAPI CD-RW, DVD-R/RW, DVD-RAM into Firewire and USB 2.0 interfaced external devices.

Push Lock Door


Front push lock door for dustproofing

Compact size


Dimensions only 24.2 x 16.4 x 6.14 cm (9.5 x 6.5 x 2.4 inch) . Smaller than any other existing 5.25" enclosures.

Compatibility

Built-in well designed 1394/ USB 2.0 bridge board to offer the highest compatibility and reliability. It works with Microsoft Windows98 SE, Windows ME, Windows 2000, Windows XP and Mac OS 9, OS/X.



Push lock door for dust proofing



Firewire/ USB 2.0 combo bridge board built-in



Speedzter 5 back panel



Stackable

Features:

- ❖ Convert IDE/ ATAPI device into IEEE 1394/ USB 2.0 Interface device
- ❖ 400 Mbps IEEE 1394 Transfer Rate
- ❖ 480Mbps USB 2.0 Transfer Rate
- ❖ Plug & Play and Hot-swapping capability
- ❖ Enclosure built-in Stereo Audio Ports.
- ❖ External 5V/ 12V DC power adapter
- ❖ Microsoft Windows98 SE, Windows ME, Windows 2000, Windows XP and Mac OS compatible
- ❖ Support CD-RW, DVD-R/RW, DVD-RAM, Hard Disk ATAPI/ IDE Interface device

Specifications:

IEEE 1394 Interface:

IEEE 1394a compliant. Support data transfer rate up to 400 Mbps. SBP-2 Target Revision 4 compliant..

USB 2.0 Interface:

USB2.0 EHCI based USB 2.0 compliant solution. transfer rate up to 480 Mbps,

IDE Interface:

USB2.0 : ATAPI/ATA-66
IEEE-1394 : ATAPI/ATA-100

Compatible ATAPI Device:

ATAPI/ATA devices: CD-ROM, CD-R, CD-RW, DVD-ROM, DVD-RAM, DVD-R/RW, DVD+RW, Hard Disk, MO Drive, Jaz, Zip, Tape Back-up

Power Supply

External Type Universal Auto Switching power supply
Operational Voltage : 5V 1.5A, 12V 1.5A DC

Rear Panel Connectors :

6-pin IEEE 1394 connector x 2
USB connector x 1
Stereo audio connector x 2 (L and R)
Power connector x 1
On/ Off Switch x 1

Enclosure Color

Blue + Silver
Customized colors

Dimension (L x W x H)

24.2 x 16.4 x 6.14 cm (9.5 x 6.5 x 2.4 inch)

Operating Temperature

0°C to 50°C

Operating Humidity

5% to 95% non-condensing

Operating System

Win98 SE, WinME, Win2k, Windows XP, Mac OS/9.X, Mac OS/X

Speedzter 5 available models

EU5 : USB 2.0 interface only

EF5 : IEEE 1394 interface

EFU5 : IEEE 1394 + USB 2.0 combo interface